



Frame size number	15.5	15.5	17.5	17.5	18.5	18.5	19.5	19.5	21.5	21.5
Frame size letter	S	S	M	M	ML	ML	L	L	XL	XL
Geometry position	Low	High	Low	High	Low	High	Low	High	Low	High
Wheel size	27.5"	27.5"	27.5"	27.5"	27.5"	27.5"	27.5"	27.5"	27.5"	27.5"
A — Seat tube	39.4	39.4	41.9	41.9	44.5	44.5	47.0	47.0	52.1	52.1
B — Seat tube angle	67.9°	68.5°	68.0°	68.5°	68.0°	68.5°	68.0°	68.5°	68.0°	68.5°
Effective seat tube angle	74.2°	74.7°	74.2°	74.7°	74.2°	74.7°	74.2°	74.7°	74.2°	74.7°
C — Head tube length	9.5	9.5	10.0	10.0	10.5	10.5	11.0	11.0	12.5	12.5
D — Head angle	65.5°	66.1°	65.6°	66.1°	65.6°	66.1°	65.6°	66.1°	65.6°	66.1°
E — Effective top tube	56.2	56.0	58.8	58.6	60.4	60.3	62.5	62.4	64.9	64.8
F — Bottom bracket height	34.9	35.6	34.9	35.6	34.9	35.6	34.9	35.6	34.9	35.6
G — Bottom bracket drop	1.6	.94	1.6	.94	1.6	.94	1.6	.94	1.6	.94
H — Chainstay length	43.5	43.3	43.5	43.3	43.5	43.3	43.5	43.3	43.5	43.3
I — Offset	4.6	4.6	4.6	4.6	4.6	4.6	4.6	4.6	4.6	4.6
J — Trail	11.5	11.2	11.5	11.2	11.5	11.2	11.5	11.2	11.5	11.2
K — Wheelbase	114.0	113.9	116.7	116.6	118.4	118.3	120.6	120.5	123.2	123.1
L — Standover	73.4	73.9	76.6	77.1	76.8	77.3	76.5	77.0	76.9	77.5
M — Frame reach	39.5	40.1	42.0	42.6	43.5	44.1	45.5	46.1	47.5	48.1
N — Frame stack	58.7	58.3	59.2	58.8	59.6	59.2	60.1	59.7	61.5	61.0